



SUHNER® DATA LINE PROTECTOR DATA SHEET

TYPE 3414.99.0003

Article number: 23041821 Rev: a

Description

Data Line protector

Hybrid Protector

Shield and Ground separated

Patch cable included

Cat 5e specified



Product Configuration

Connectors RJ45 jack (female)
Mounting and grounding MH154, screw M4, grounding cable

Technical Data

Impedance:	100 Ω
Frequency range	DC to 100 MHz
Insertion loss	≤ 0.5 dB
Voltage rating:	per Pair ± 6 V max.
Current rating	per Pair 1.5 A max.
Current handling capability	IEC 61000-4-5: Shield – Ground 6 kA Line – Ground 2.5 kA Line – Line 100 A
Related protection levels	IEC 61000-4-5: Shield – Ground 700 V Line – Ground 700 V Line – Line 20 V
Clamping voltage	Shield – Ground 90 V Line – Ground 90 V Line – Line 15 V
Response time	2 ns
Operating temperature	-40°C to + 85°C
Waterproof degree	IP20 (according to IEC 60529, data refer to the coupled state)

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists. All product data is not binding and subject to change at any time. The products of HUBER + SUHNER are tested in a laboratory environment against specific standards and test procedures. Any guarantee for specific applications or environmental conditions requires a separate written agreement.



HUBER+SUHNER

HUBER+SUHNER AG
Protection+Federline Components
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 47 51
www.hubersuhner.com

Issued: 20.5.2003 09:19



SUHNER® DATA LINE PROTECTOR DATA SHEET

Piece Parts

Housing

Material

Aluminum alloy AlMgSi 0.5


Surface Plating

chromatized

Remarks:

- Each pair protected with gas capsules and TVS diodes (all 8 Pins of the RJ45 connector protected)
- Grounding screws included
- Application with shielded or unshielded twisted pair cables possible (RJ45 shields are connected)
- For proper function the Protector has to be connected to ground via housing or shield

Circuit diagram



Attachment

Related Documents

Outline drawing

23041823

Mounting/ Grounding instruction

23040774

WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.

All product data is not binding and subject to change at any time. The products of HUBER + SUHNER are tested in a laboratory environment against specific standards and test procedures. Any guarantee for specific applications or environmental conditions requires a separate written agreement.



HUBER+SUHNER

HUBER+SUHNER AG
Protection+Federline Components
CH-9100 Herisau
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 47 51
www.hubersuhner.com

Issued: 20.5.2003 09:19